


Aqua Wandfliesenlack

- Aqua Wall Tile Lacquer -

Interior

Water-based 1-component 1-pot system

General Description

Type of material:	Water-based 1-pot system with special acrylate base
Range of uses:	Primer and cover coats for ceramic substrates. No separate primer required. For decorative new designs on old wall tiles, tiled sections or tiled bases. Our transparent finishing coat Jansen Aqua Wall Tile Lacquer Finish must be used as a final coat in wet room areas and tiled sections in kitchens.
Product properties:	Excellent adhesion on matt, semi gloss and gloss tiles. Creates a robust, scratch-resistant surface.
Colour shades:	White  MIX
Packaging sizes:	750 ml, 2.5 ltr

Technical Data

Binder base:	Special acrylate
Pigment base:	Titanium dioxide and light-resistant coloured pigments
Density:	1.27 g/cm ³
Gloss level:	semi gloss
Viscosity:	slightly thixotropic
Thinner:	up to max. 5% water
Application Temperature:	Above + 7°C for objects and ambient air

Drying:	(At 20°C and 60% relative humidity) Dust-dry: ca. 1 hour May be coated over: ca. 4-6 hours Fully resilient: after ca. 4 days These values can vary significantly depending on temperature and humidity.
Spreading rate:	Ca. 10 - 12 m ² /l per coat
GISCODE:	BSW30

Method of processing

Substrate preparation:	<p>The substrate must be dry, stable, firm and free from separating substances (oil, grease, wax, dust etc.). Silicone joints must be removed completely and replaced by permanently elastic joint sealers with an acrylic or polyurethane base that can be coated over.</p> <p>Wipe the surface to be painted with warm water mixed with a small quantity of detergent. Do not use an alkaline cleaner. Sand the tile surface with a fine-grain abrasive. Washing and sanding can be combined in a direct wet grinding.</p> <p>Connecting joints on bathtubs, showers and washbasins should be resealed with sanitary silicone once the coat has dried completely.</p> <p>The substrate preparation and the coat application must be performed to current scientific and technological standards. Please observe the current BFS (German Federal Commission for protection of paint and material assets) data sheets, as well as the VOB (German Construction Contract Procedures), Part C, DIN 18363 Painting and coating work.</p>
Coating structure:	<p>Jansen Aqua Wall Tile Lacquer has a consistency ready for brushing and can be thinned with max. 5% water depending on the application. Apply Jansen Aqua Wall Tile Lacquer two to three times depending on the application area and the colour shade.</p> <p>Do a trial coating before final application.</p>
Final coat (wet areas)	<p>For wet rooms only (splashing water range in shower cubicles and above bathtubs), we recommend 1-2 transparent coat(s) of our Jansen Aqua Wall Tile Lacquer Finish.</p> <p>Not suitable for surfaces where water can remain for a long time. A coat of Aqua Wall Tile Lacquer applied to tiled sections in kitchens generally needs to be protected with Jansen Aqua Wall Tile Lacquer Finish.</p> <p>The top coat should only be applied 48 hours after the last Aqua Wall Tile Lacquer coat.</p>

Coating methods:	<u>Brushing</u> : Use brush with plastic bristles for painting <u>Rolling</u> : Use short pile mohair rollers.
Cleansing of tools:	Immediately if possible, with water. Clean intermittently when used for longer periods or before breaks. Do not allow paint to dry.
Later cleaning of the finished surface:	Earliest clean with clear water: after 3 days Earliest clean with bathroom cleaner: after 7 days Test bathroom cleaners first in an unobtrusive place. Exposure time must not exceed 5 minutes.
Storage:	Cool, dry and protected from frost. Seal opened containers well.
VOC-Value:	EU limit for this product (Cat. A/d): 140 g/l VOC (2010). This product contains max. 75 g/l VOC.

Identification Marking: Please take note of our updated Safety Data Sheet available on the Internet at www.jansen.de / www.jansen-lacke.at

The technical information was compiled in accordance with the latest state of the art. An obligation for the general validity of the individual recommendations cannot, however, be accepted as the application and processing methods do not lie within our influence and the varying states of the substrates each require a decision as to the method of working suitable for workman and trade. The recommendations do not release the customer from the task of accepting responsibility for checking the products of the supplier company as to their suitability for the foreseen use. Applicable are the "General Terms and Conditions of Delivery and Payment in the Paint Industry" in the recommendation approved by the Federal Cartel Office (Bundeskartellamt) on 1. January 2018. On publication of this data sheet, all previous data sheets for this product become invalid.

UST-IdNr.: DE147923895

P.A. Jansen GmbH u. Co., KG / Hochstadenstraße 22 / D-53474 Ahrweiler
Tel +49 2641 3897-0 / Telefax +49 2641 3897-28

Jansen GmbH / Zetschegasse 13 / A-1230 Wien
Tel +43 1 6620956 / Telefax +43 1 6620956-12