

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 32-0255  
Print date 07.05.2020  
Version 66.62

Compact-Lasur  
Revision date 30.04.2020  
Issue date 30.04.2020

EN  
Page 1 / 9

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Article No. (manufacturer/supplier): 32-0255  
Trade name/designation Compact-Lasur  
mahagoni  
seidenglänzend

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Relevant identified uses:**

Varnish / paint

**Uses advised against:**

Aware of any other information

**1.3. Details of the supplier of the safety data sheet**

**Supplier (manufacturer/importer/only representative/downstream user/distributor)**

P.A. Jansen GmbH u. Co., KG  
Maler-Spezialprodukte  
Hochstadenstraße 22  
D-53474 Bad Neuenahr-Ahrweiler  
Telephone: +49 2641 3897-0  
Telefax: +49 2641 3897-28  
Homepage: www.jansen.de

**Department responsible for information:**

laboratory  
E-mail (competent person) sicherheitsdatenblatt@jansen.de

**1.4. Emergency telephone number**

Emergency telephone number +49 2641 3897-51  
Only available during office hours.

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

**2.2. Label elements**

The product is classified and labelled according to EC directives or corresponding national laws.

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**

**Hazard statements**

No data available

**Precautionary Statements**

No data available

**Hazard components for labelling**

No data available

**Supplemental hazard information**

EUH208 Contains Phthalic anhydride. May produce an allergic reaction.  
EUH210 Safety data sheet available on request.

**2.3. Other hazards**

No information available.

**SECTION 3: Composition / information on ingredients**

**3.2. Mixtures**

**Description** alkyd resin varnish

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

**EC No.** **REACH No.**

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 32-0255 Compact-Lasur  
Print date 07.05.2020 Revision date 30.04.2020  
Version 66.62 Issue date 30.04.2020

EN  
Page 2 / 9

CAS No. INDEX No.	Designation classification: // Remark	Wt %
918-481-9	01-2119457273-39 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics Asp. Tox. 1 H304	35 - 50
245-018-1 22464-99-9	01-2119979088-21 2-Ethylhexanacid, Zirconiumsalt Repr. 2 H361d	0,15 - 0,2

**Additional information**

Full text of classification: see section 16

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

**In case of inhalation**

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

**Following skin contact**

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

**After eye contact**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

In all cases of doubt, or when symptoms persist, seek medical advice.

**4.3. Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

**Unsuitable extinguishing media**

strong water jet

**5.2. Special hazards arising from the substance or mixture**

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

**5.3. Advice for firefighters**

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Cool closed containers that are near the source of the fire.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

**6.3. Methods and material for containment and cleaning up**

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

Article No.: 32-0255 Compact-Lasur  
Print date 07.05.2020 Revision date 30.04.2020  
Version 66.62 Issue date 30.04.2020

EN  
Page 3 / 9

6.4. **Reference to other sections**

Observe protective provisions (see section 7 and 8).

**SECTION 7: Handling and storage**

7.1. **Precautions for safe handling**

**Advices on safe handling**

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

**Further information**

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. **Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

**Hints on joint storage**

Keep away from strongly acidic and alkaline materials as well as oxidizers.

**Further information on storage conditions**

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. **Specific end use(s)**

Observe technical data sheet. Observe instructions for use.

**SECTION 8: Exposure controls/personal protection**

8.1. **Control parameters**

**Occupational exposure limit values**

Silicon dioxide

EC No. 231-545-4 / CAS No. 112945-52-5

WEL, TWA: 2,4 mg/m<sup>3</sup>

Remark: (Silica, amorphous; respirable fraction)

WEL, TWA: 6 mg/m<sup>3</sup>

Remark: (Silica, amorphous; inhalable fraction)

**Additional information**

TWA : long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

**DNEL:**

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

EC No. 918-481-9

DNEL long-term dermal (systemic), Workers: 300 mg/kg

DNEL long-term oral (repeated), Consumer: 300 mg/kg

DNEL long-term dermal (systemic), Consumer: 300 mg/kg

DNEL long-term inhalative (systemic), Consumer: 900 mg/m<sup>3</sup>

8.2. **Exposure controls**

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

**Personal protection equipment**

Article No.: 32-0255  
Print date 07.05.2020  
Version 66.62

Compact-Lasur  
Revision date 30.04.2020  
Issue date 30.04.2020

EN  
Page 4 / 9

#### **Respiratory protection**

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number. Observe the wear-time limits as specified by the manufacturer. Recommended respiratory protection articles : Inadequately ventilated workplaces and spraying procedures are necessary. Fresh air mask or short-time work combination filter A2-P2 are recommended.

#### **Hand protection**

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

#### **Eye/face protection**

Wear closely fitting protective glasses in case of splashes.

#### **Body protection**

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

#### **Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

#### **Environmental exposure controls**

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

### **SECTION 9: Physical and chemical properties**

#### **9.1. Information on basic physical and chemical properties**

##### **Appearance:**

**Physical state:** Liquid  
**Appearance:** Liquid  
**Colour:** refer to label

**Odour:** characteristic

**Odour threshold:** No data available

**pH at 20 °C:** no information

**Melting point/freezing point:** No data available

**Initial boiling point and boiling range:** 119 °C  
Source: 1-methoxy-2-propanol

**Flash point:** > 61 °C  
Method: EN ISO 1523

**Evaporation rate:** No data available

##### **flammability**

**Burning time (s):** No data available

##### **Upper/lower flammability or explosive limits:**

**Lower explosion limit:** 0,6 Vol-%  
Method: literature value  
Source: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

**Upper explosion limit:** 7 Vol-%  
Method: literature value  
Source: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

**Vapour pressure at 20 °C:** 0,6 mbar  
Source: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

**Vapour density:** No data available

**Relative density:**  
**Density at 20 °C:**

0,94 g/cm<sup>3</sup>  
Method: DIN 53217

Article No.: 32-0255 Compact-Lasur  
Print date 07.05.2020 Revision date 30.04.2020  
Version 66.62 Issue date 30.04.2020

EN  
Page 5 / 9

<b>Solubility(ies):</b>	
<b>Water solubility (g/L) at 20 °C:</b>	<b>insoluble</b>
<b>Partition coefficient: n-octanol/water:</b>	<b>see section 12</b>
<b>Auto-ignition temperature:</b>	<b>231 °C</b> Source: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics
<b>Decomposition temperature:</b>	<b>No data available</b>
<b>Viscosity at °C:</b>	<b>thixotrop</b>
<b>Kinematic viscosity at 20 °C::</b>	<b>&gt; 20,5 mm<sup>2</sup>/s</b>
<b>Explosive properties:</b>	<b>No data available</b>
<b>Oxidising properties:</b>	<b>No data available</b>
9.2. <b>Other information</b>	*
<b>Solid content (%):</b>	<b>58 Wt %</b>
<b>solvent content:</b>	
<b>Organic solvents:</b>	<b>42 Wt %</b>
<b>Water:</b>	<b>0 Wt %</b>

#### **SECTION 10: Stability and reactivity**

- 10.1. **Reactivity**  
No information available.
- 10.2. **Chemical stability**  
Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.
- 10.3. **Possibility of hazardous reactions**  
Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.
- 10.4. **Conditions to avoid**  
Hazardous decomposition byproducts may form with exposure to high temperatures.
- 10.5. **Incompatible materials**  
not applicable
- 10.6. **Hazardous decomposition products**  
Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

#### **SECTION 11: Toxicological information**

Classification according to Regulation (EC) No 1272/2008 [CLP]  
No data on preparation itself available.

##### 11.1. **Information on toxicological effects**

###### **Acute toxicity**

Silicon dioxide

oral, LD50, Rat: > 5000 mg/kg

Method: OECD 401

dermal, LD50, Rabbit: > 5000 mg/kg

inhalative (dust and mist), LC50, Rat: > 58,8 mg/l (4 h)

Method: OECD 403

2-Ethylhexanacid, Zirconiumsalt

oral, LD50, Rat: > 5000 mg/kg

dermal, LD50, Rabbit: > 5000 mg/kg

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

oral, LD50, Rat: > 5000 mg/kg

Method: OECD 401

dermal, LD50, Rabbit: > 5000 mg/kg

Method: OECD 402

inhalative (vapours), LC50, Rat: > 4951 mg/l (4 h)

Article No.: 32-0255 Compact-Lasur  
Print date 07.05.2020 Revision date 30.04.2020  
Version 66.62 Issue date 30.04.2020

EN  
Page 6 / 9

Method: OECD 403

**Skin corrosion/irritation; Serious eye damage/eye irritation**

Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation**

Based on available data, the classification criteria are not met.

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Based on available data, the classification criteria are not met.

**STOT-single exposure; STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics  
Aspiration hazard

**Practical experience/human evidence**

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

**Overall Assessment on CMR properties**

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

**Remark**

There is no information available on the preparation itself .

**SECTION 12: Ecological information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

There is no information available on the preparation itself .

Do not allow to enter into surface water or drains.

**12.1. Toxicity**

Silicon dioxide

Fish toxicity, LC50, Brachydanio rerio (zebra-fish): > 10000 mg/l (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna: > 1000 mg/l (48 h)

Method: OECD 202

Algae toxicity, EC50, Desmodesmus subspicatus: > 10000 mg/l (72 h)

Method: OECD 201

2-Ethylhexanacid, Zirconiumsalt

Fish toxicity, LC50, Oryzias latipes: > 100 mg/l (96 h)

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): > 1000 mg/l (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna: > 1000 mg/l (48 h)

Method: OECD 202

Algae toxicity, EC50, Pseudokirchneriella subcapitata: > 1000 mg/l

Method: OECD 201

**Long-term Ecotoxicity**

Silicon dioxide

Fish toxicity, NOEC: 86,03 mg/l (30 d)

**12.2. Persistence and degradability**

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Biodegradation: 80 % (28 d); evaluation Readily biodegradable (according to OECD criteria)

Method: OECD 301F

**12.3. Bioaccumulative potential**

Toxicological data are not available.

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 32-0255 Compact-Lasur  
Print date 07.05.2020 Revision date 30.04.2020  
Version 66.62 Issue date 30.04.2020

EN  
Page 7 / 9

**12.4. Mobility in soil**

Toxicological data are not available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Other adverse effects**

No information available.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Appropriate disposal / Product Recommendation**

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

**List of proposed waste codes/waste designations in accordance with EWC**

080111\* Waste paint and varnish containing organic solvents or other dangerous substances

\*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

**Appropriate disposal / Package Recommendation**

**Recommendation**

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

**SECTION 14: Transport information**

**This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).**

**14.1. UN number**

No data available

**14.2. UN proper shipping name**

**14.3. Transport hazard class(es)**

No data available

**14.4. Packing group**

No data available

**14.5. Environmental hazards**

Land transport (ADR/RID)

No data available

Marine pollutant

No data available

**14.6. Special precautions for user**

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

**Further information**

**Land transport (ADR/RID)**

tunnel restriction code

-

**Sea transport (IMDG)**

EmS-No.

No data available

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

\*

**EU legislation**

**Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]**

This product is not classified according to Directive 2012/18/EU.

**Directive 2004/42/EC on the limitation of emissions of volatile organic compounds**

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 32-0255 Compact-Lasur  
Print date 07.05.2020 Revision date 30.04.2020  
Version 66.62 Issue date 30.04.2020

EN  
Page 8 / 9

VOC product category: (Cat. A/e) ; VOC limit value: 400 g/l  
Maximum VOC content (g/L) of the product in a ready to use condition: 400

**National regulations**

**Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.  
Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

15.2. **Chemical Safety Assessment**

**For the following substances of this mixture a chemical safety assessment has been carried out:**

EC No. CAS No.	Designation	REACH No.
918-481-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics	01-2119457273-39
245-018-1 22464-99-9	2-Ethylhexanacid, Zirconiumsalt	01-2119979088-21

**SECTION 16: Other information**

**Full text of classification in section 3:**

Asp. Tox. 1 / H304                      Aspiration hazard                      May be fatal if swallowed and enters airways.  
Repr. 2 / H361d                      Reproductive toxicity                      Suspected of damaging the unborn child.

**Abbreviations and acronyms**

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

**Data sources:**

Data arise from reference works and literature.

**Further information**

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

\* Data changed compared with the previous version



**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 32-0255 Compact-Lasur  
Print date 07.05.2020 Revision date 30.04.2020  
Version 66.62 Issue date 30.04.2020

EN  
Page 9 / 9

---